



Features

- 1. Embedded outdoor KIOSK design, especially for **MARINE Projects**.
- 2. Adopt **5 Wires Resistive Touch**, high sensitivity, and fast response.
- 3. **1000nits (cd/m²)**, sunlight readable, high brightness.
- 4. **DC9-36V Wide Voltage**, industrial grade. (DC12V, DC12-24V optional)
- 5. Wide temperature range: operating: **-20 to 70°C**, storage: -30 to 80°C.

Specification

Screen	LCD Panel	Panel size	15-inch
		Resolution	1024*600 16:9
		Brightness (cd/m ²)	1000nits, sunlight-readbale
		Contrast ratio	800:1 (Typ.)
		View Angle	80°/80°/80°/80° (R/L/U/D)
		Surface Treatment	Anti-glare
	Touch	Light Sensor	Auto-dimming Optional
		Touch Type	5 wires Resistive Touch
		Touch Optional	10 points Capacitive Touch
		Surface Hardness	≥3H
Touch Interface	USB		
Working Life	≥50 million times		

Environment	Temperature	Operating: -20°C to 70°C, storage: -30°C to 80°C
	Humidity	10%~90% @ 30°C, non-condensing

I/O Interfaces	1xFUSE, 1xDVI, 1xVGA, 3xCVBS(Composite Video) for AV, 1xRS232 1xUSB 1xFront OSD Control, 1xOn/Off, 1xVR Knob
Power Supply	DC9-36V (DC 12v, 12-24v Optional)

Enclosure	Material	Aluminum Alloy
	Color	Black
	VESA	75x75mm/100x100mm
	IP grade	Front IP65 Waterproof
Back design	A rubber ring with drainage channels (Optional)	

Demision	Net weight	3.62kg
	Gross weight	/
	Product size	352.8x303.3x56mm
	Packing size	/

Packaging	1xMonitor, 1xDC Power Cable, 1xAdaptor, 1xUSB Cable, 1xHDMI/VGA
OS	Support Windows 7/8/10, WES, Linux, Ubuntu, Debian, Android, etc.
Mountings	Embedded mounting screws
	Wall mounting brackets, Desk stand holder (optional)
Warranty	1-year free warranty

