



Features

- 1. NEMA4/IP67 waterproof and dustproof design, all interfaces with waterproof connectors
- 2. Aluminum Alloy enclosure, more resistant to corrosion, shock and vibration
- 3. Adopting EETI solution capacitive touch or no touch + industrial-grade, high-performance
- 4. DC 12V power supply (DC24V, 9-36V Optional), support power-on boot, 7x24hours
- 5. High brightness 1500nits sunlight-readable for outdoor application

Specification

Screen	LCD Panel	Panel size	24"
		Resolution	1920*1080 16:9
		Brightness (cd/m ²)	1500nits, sunlight-readable
		Contrast ratio	1000:1 (Typ.)
		View Angle	80°/80°/80°/65° (R/L/U/D)
	Touch	Touch Type	10 Points Capacitive Touch
		Touch Optional	No Touch / 5 Wires Resistive Touch
		Surface Hardness	G+G ≥7H, or ≥3H
		Touch Interface	USB
		Working Life	≥50 million times
Surface Treatment	Anti-glare/Anti-reflection Optional		
Glass Treatment	Optical Bonding Optional		

Environment	Temperature	Operating: -20 to 70°C, storage: -30 to 70°C
	Humidity	10%~90% @ 30°C, non-condensing

I/O Interfaces	1xHDMI, 1xDC12V, 1xUSB, 1xAudio, 1xVGA
Power Supply	DC12V (DC24v, 9-36v Optional)


Enclosure	Material	Aluminum Alloy+ Back High Strength Cold Rolled Steel Meta
	Color	Black
	VESA	75mm*75mm/100mm*100mm
	IP grade	FULL IP67 Waterproof
Dimension	Net weight	5kg
	Gross weight	6kg
	Product size	591.4x370.9x43.6mm
	Packing size	700x180x480mm

Packaging	1xMonitor, 1xDC Power Cable, 1xAdaptor, 1xHDMI, 1xVGA
OS	Support Windows 7/8/10, WES, Linux, Ubuntu, Debian, Android, etc.
Mountings	Desk stand holder
	Wall mounting brackets, Embedded mounting screws (optional)
Warranty	1-year free warranty

Sizes Optional

7" 8"	10.1"	12.1"	13.3"	15" 15.6"	17"	19"	21.5"
1024*600 1024*768	1280*800	1024*768 1280*800	1920*1080	1024*768 /1920*1080	1280*1024	1280*1024	1920*1080
4:3	16:10	4:3	16:9	4:3 16:9	4:3	4:3	16:9

Drawing



Accessories

- 1x Monitor
- 1x HDMI Cable
- 1x Power Cable
- 1x Adaptor
- 1x USB Cable