



Features

- 1. NEMA4/IP67 waterproof and dustproof design, all interfaces with waterproof connectors
- 2. Aluminum Alloy enclosure, more resistant to corrosion, shock and vibration
- 3. Adopting no touch for CCTV function+ industrial-grade, high-performance
- 4. DC 12V power supply (DC24V, 9-36V Optional), support power-on boot, 7x24hours
- 5. High brightness 1000nits sunlight-readable for outdoor application

Specification

Screen	LCD Panel	Panel size	18.5"
		Resolution	1366*768 16:9
		Brightness (cd/m ²)	1500nits, sunlight-readable
		Contrast ratio	1000:1 (Typ.)
		View Angle	80°/80°/80°/65° (R/L/U/D)
	Touch	Touch Type	No Touch
		Touch Optional	Capacitive TouchNo / Resistive Touch
		Surface Hardness	≥3H; or G+G ≥7H
		Touch Interface	USB
		Working Life	≥50 million times
Surface Treatment	Anti-reflection /AF Optional		
Glass Treatment	Optical Bonding Optional		

Environment	Temperature	Operating: -20 to 70°C, storage: -30 to 70°C
	Humidity	10%~90% @ 30°C, non-condensing

I/O Interfaces	AV1, AV2, AV3, DC12V
Power Supply	DC12V (DC24v, 9-36v Optional)

Enclosure	Material	Aluminum Alloy + Back High Strength Cold Rolled Steel Meta
	Color	Black
	VESA	75mm*75mm/100mm*100mm
	IP grade	FULL IP67 Waterproof
Dimension	Net weight	6kg
	Gross weight	7.5kg
	Product size	/
	Packing size	680x240x250mm

Packaging	1xMonitor, 1xDC Power Cable, 3xAV Cables
OS	Support Windows 7/8/10, WES, Linux, Ubuntu, Debian, Android, etc.
Mountings	Desk stand holder
	Wall mounting brackets, Embedded mounting screws (optional)
Warranty	1-year free warranty

Sizes Optional

7" 8"	10.1"	12.1"	13.3"	15" 15.6"	17"	19"	21.5"
1024*600 1024*768	1280*800	1024*768 1280*800	1920*1080	1024*768 /1920*1080	1280*1024	1280*1024	1920*1080
4:3	16:10	4:3	16:9	4:3 16:9	4:3	4:3	16:9

Drawing

Accessories

- 1x Monitor
- 3x AV Cable
- 1x Power cable